

PFAFF[®] Industrial



5625

Special single-needle chainstitch sewing head for the use on TAPE EDGE sewing units

Extremely reliable and powerful machine head - Made in Germany

Features:

- Special machine head with unison feed for the use on production units for mattresses
- Looper working in feeding direction (INLINE)
- High top feed stroke: max. 7 mm
- Sewing foot clearance: max. 14 mm
- Special shortened free-arm version
- Maintenance is kept to a minimum due to a reliable fresh-oil lubrication system. The oil distribution system is specifically designed for the angled machine mounting.
- Anti-friction bearings used on all main components
- Sewing head is weight optimized for sewing units
- Stitch type 401 = Single-needle chainstitch (-840/01)
- Options: LED-Light + needle cooler

Specifications:

- Max. sewing speed: 3,500 s.p.m.
- Stitch type: 401
- Needle system: SY 4112
- Needle size: 180 Nm
- Max. stitch length: 8.5 mm
- Presser foot lift (by hand): 11 mm
- Presser foot lift (via cylinder): 11 mm
- Thread size, max.: 11/3 syn.

Versions	Mechanical presser foot lift and tension release	Pneumatically presser foot lift and tension release
	-657/01	-657/02-906/07
5625-840/01	x	
5625-840/01		x



PFAFF Industriesysteme und Maschinen GmbH
 Hans-Geiger-Str. 12 · IG Nord · D-67661 Kaiserslautern
 Tel.: +49-6301/3205-0 · Fax: +49-6301/3205-3171
 E-mail: info@pfaff-industrial.com · www.pfaff-industrial.com